

XL-2T

7 Zone Control / Communicator



Designed for easy installation and homeowner convenience, the fully-featured XL-2T control panel is the next generation of the popular XL-2 series. For price and performance, it's the best control panel in its class.

Remote or local troubleshooting is made quick and simple with the XL-2T's large event buffer. The control panel is engineered to maintain up to 76 events, each of which is identified with a time and date stamp.

FEATURES

- Unattended downloading
- 7 fully programmable zones
- 78 event history with time and date stamp
- Auto arming options based on AC real time clock
- 2 programmable trigger outputs
- 2 channel siren driver built in
- 2 Fully programmable entry timers
- SIA false alarm reduction features
- Bell supervision
- Temporal bell option

SYSTEM COMPONENTS

- XL-2TLT: Includes Control/Communicator. Transformer and Keypads available separately
 - XL-2T: Includes Control/Communicator and 12V 20VA Transformer
 - XL-2TX: PC Board only
 - XK-406: 6 zone LED keypad, surface mount, individual LEDs for zones and system status. (Also available, model XK-206)
 - XL-4600RM: 6 zone LED metal keypad, flush mount, individual LEDs for zones and system status
 - XL-4600SM: 6 zone LED plastic keypad, surface mount, individual LEDs for zones and system status
 - XK-5LC: 2 line by 12 large characters LCD supertwist backlit display. (Also available, model XK3LC)
 - XK-7LC: 2 line by 12 large characters LCD supertwist backlit display, includes armed status LED
 - 6615: 6 zone LED legend style keypad, surface mount individual LEDs for zone and system status
- Note: If you use XL-4600RM, XL-4600SM or 6615 you cannot use any other types

XL-2T

7 Zone Control / Communicator

SPECIFICATIONS

Zones

- 7 fully programmable zones, each selectable for EOL supervision, NO or NC devices
- Four emergency keypad conditions (fire, panic, aux, duress)
- Versatile zone types:
Controlled zone types include; Instant, exit/entry, interior, day, and keyswitch, with options for fast loop response, restore and chime by zone. 24 hour zone types include: fire, burglary, silent, trouble, medical
- Programmable central station reporting codes per zone
- Smoke reset and verification features
- Cross zone capabilities
- New stay delay zone type

Additional Features

- Cancel code feature
- Installer walk test feature
- Real time clock with reminder when time needs to be reset
- Chime on/off feature through keypad
- Keypad tamper function with optional CS transmission
- Swinger shutdown option
- System stabilization time prevents false alarms during powerup
- NFPA temporal bell
- Arm while faulted
- Supervised bell output
- 78 Event Log
- Paging Format

User Codes:

- 15 user codes
- Ambush and door strike codes
- Open/close by user ID
- Unique O/C codes for all users

Programming / Remote Operations

- Remote commands include: arm, disarm, bypass zones, change user codes, read system status
- Remote operations can be performed through PC Downloader
- Upload/download remote operations of all system features and functions. ALL ON A SINGLE CALL. With FBII Answering Machine Bypass
- Remote and/or unattended downloading
- On-site programming directly through keypad (LED or LCD)
- CSID and installer code, anti-takeover feature

Keypads

- Individual LEDs show status of each zone with indications of ALARM, TROUBLE BYPASS and NOT READY conditions
- English LCD keypad displays system status in 2 line by 16 character readout with customized 12 character zone descriptors (LCD keypads include XK-5LC, XK-3LC and XK-7LC)

Central Station Communications

- Two CS account numbers (3 or 4 digits)
- Pulse formats include: 3x1, 4x1, 4x2, Expanded: Speeds 10, 20, 40PPS with or without parity
- FBI Superfast
- Split and dual reporting option for openings and closings
- Test options include daily, weekly, 27, 60 or 90 day, hourly intervals test by time, event

Power Specifications

- Watchdog circuitry insures integrity of microprocessor
- Total aux. power: 500 mA. regulated
- Transformer: 12V 20VA

Listings*

- Residential UL Household Combination Burglary/Fire (XL-2T)
- UL Mercantile Burglary Listing: Local Grade A, Police Connect Grade A, Grade AA
- California State Fire Marshal (CSFM)*
- CE

*Listing pending as of printing date

ORDERING:

XL-2T

7 Zone Control / Communicator

Honeywell Security & Custom Electronics

Honeywell International Inc.
PO Box 9035
Syosset, NY 11791
www.honeywell.com

F/XL2TEX/D
July 2005
©2005 Honeywell International Inc.

Honeywell